ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

SCC Accredited CB-P/S OCPS Accrédité CCN

America

C E R T I F I C A T E

No. U8C 014542 0004 Rev. 00

Holder of Certificate: **Braviisol D.M. S.r.l.**
S.S. Adriatica 16
KM 314,600
60022 Castelfidardo (AN)
ITALY

Certification Mark:

Product: Mobile elevating work platform
Aerial Work Platform

This product was voluntarily tested to the relevant safety requirements referenced on this certificate. It can be marked with the certification mark above. The mark must not be altered in any way. This product certification system operated by TÜV SÜD America Inc. most closely resembles system 3, as defined in ISO/IEC 17067. Certification is based on the TÜV SÜD "Testing, Certification, Validation and Verification Regulations (TCVVR)". TÜV SÜD America Inc. is accredited by the Standards Council of Canada to ISO/IEC 17065.

Test report no.: 72199452-000

Date, 2024-10-28

(Adrian Rabago Valenzuela)

TÜV SÜD America, Inc. • 401 Edgewater Place Suite #500 • Wakefield • MA 01880 • USA

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

SCC Accredited CB-P/S OCPS Accrédité CCN

TÜV SÜD America

C E R T I F I C A T E

No. U8C 014542 0004 Rev. 00

Model(s): LUI HD

Brand Name: BRAVI PLATFORMS

Tested according to: CSA B354.6:2017

Parameters:

Machine Gross Weight (Vehicle Empty)	1234 lb./560 kg
Occupants: (persons permitted on the platform)	1
Group	A
Type	3
Maximum wind speed	28 mph / 12.5 m/s
Maximum platform height	9.6 ft/ 293 cm
Gradeability	35%
Max operational height (based on an operator standing in basket reaching overhead)	16.15 ft/ 493 cm
Machine Height (Platform Completely Lowered)	5.7ft/ 173 cm
Machine Length	4.3 ft/ 132 cm
Machine Width	2.4 ft/ 76 cm
Maximum speed (lowered)	1.9 mph –3 km/h
Maximum speed (elevated)	0.35 mph – 0.6 km/h
Turning Radius (Internal)	ZERO
Maximum Slope Practicable	1,5° (outdoor) 2° (indoor)
Platform Cycle Performance	Raising 16 sec Lowering 14 sec
Drive System	One-hand Proportional
Tyres	Anti-Skid Solid Rubber
Electronic Slope Control	Standard
Maximum Wheel Load	542 lbs. / 246 kg.
Maximum platform capacity	500 lbs./ 227 kg.
Batteries	N 02, 12V 85Ah@20h
Power Supply	24Vdc
Noise level: (Measurement uncertainty = 5 dB)	70 dB (A)

TÜV SÜD America, Inc. • 401 Edgewater Place Suite #500 • Wakefield • MA 01880 • USA

TÜV®